

USYSTEM

ROOF SW LIGHT PLUS



Elementtype	Rc-waarde [m ² K/W]	Rib-afmetingen [mm]	Aantal velden	Dakhelling											
				15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
ROOF SW LIGHT PLUS CB White	2,5	20 x 70	1-velds	2020	2130	2130	2130	2115	2100	2080	2060	2145	2230	2263	2295
			meervelds*	2570	2710	2710	2710	2690	2670	2650	2630	2740	2850	2895	2940
			overstek	643	678	678	678	673	668	663	658	685	713	724	735
	3,7	20 x 102	1-velds	2540	2690	2690	2690	2670	2650	2625	2600	2705	2810	2850	2890
			meervelds*	3200	3380	3380	3380	3355	3330	3305	3280	3415	3550	3605	3660
			overstek	800	845	845	845	839	833	826	820	854	888	901	915
	4,7	20 x 126	1-velds	3020	3190	3190	3190	3170	3150	3120	3090	3210	3330	3375	3420
			meervelds*	3780	3980	3980	3980	3955	3930	3900	3870	4025	4180	4242,5	4305
			overstek	945	995	995	995	989	983	975	968	1006	1045	1061	1076
	6,3	20 x 171	1-velds	3570	3780	3780	3780	3755	3730	3695	3660	3800	3940	3993	4045
			meervelds*	4440	4700	4700	4700	4670	4640	4605	4570	4740	4910	4977,5	5045
			overstek	1110	1175	1175	1175	1168	1160	1151	1143	1185	1228	1244	1261
	7	20 x 176	1-velds	4050	4290	4295	4300	4270	4240	4205	4170	4320	4470	5000	5140
			meervelds*	5030	5320	5325	5330	5295	5260	5220	5180	5370	5560	6000	6000
			overstek	1258	1330	1331	1333	1324	1315	1305	1295	1343	1390	1500	1500

Uitgangspunten: Windgebied 2 onbebouwd
 Dakbedekking: 50 kg/m²
 * Bij meervelds overspanning moet het kleinere veld tenminste 1/3 van het grotere veld bedragen